



- GENERAL NOTES**
1. Construction shall be in accordance with the standard specifications for public works construction, 1973 edition and per City of Riverside Standard Drawings.
  2. No flagpole alterations shall be stated in the field by the Engineer.
  3. Location of the driveway approach (5'x11' 30" x 2' 30") to be determined by the name of construction as approved by the Traffic Engineer.
  4. Curb and gutter to be spaced of a 3' offset and of 25' minimum.
  5. It shall be the responsibility of the contractor to clear the right of way in accordance with the provisions of law as if applied each utility installation, irrigation lines & appurtenances and of no cost to the City.
  6. Thin edge of existing pavement where new pavement joins to a smooth transition from contractor's material to existing pavement and over lay paving as directed in the field to produce a smooth condition. Engineer estimates curbs to be 60 years.
- BENCH MARK**  
 City of Riverside No. 533 Elev. 288.445  
 at the main entrance of Arlington Pub. Library  
 5.50' to a 3" x 3" disk stamped 533 1924, approx. 1' above ground

ALBERT A. WEBB ASSOCIATES CIVIL ENGINEERS RIVERSIDE, CALIFORNIA APPROVED BY: <i>E. N. WOOD</i> DATE: 6/2/76 R.E. No. 5023 W.D. 5-121 FOR WILLIAM AUSTIN F.B. 2084		CITY OF RIVERSIDE, CALIFORNIA PUBLIC WORKS DEPARTMENT APPROVED BY: <i>[Signature]</i> DATE: 6/2/76 PRINCIPAL ENGINEER PARK DEPARTMENT TRAFFIC DIVISION CHIEF PUBLIC WORKS ENGR.		STREET PLAN AND PROFILE <b>MYERS STREET</b> ONLY CURB FROM 225' TO 377' E W/2' OF MAGNOLIA AVE ZONING CASE 68-42-284 & R-44-500 SCALE: Horiz. 1" = 20' Vert. 1" = 4' DATE: 9-19-74		ACCOUNT No. DRAWING NUMBER <b>R-1778</b> SHEET 1 OF 1 <b>74-111-A</b>
--	--	---	--	--	--	---