



- GENERAL NOTES**
- IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO CLEAR THE RIGHT OF WAY IN ACCORDANCE WITH THE PROVISIONS OF LAW AS IT APPLIES SUCH DUTY INCLUDING RELOCATION LINES AND IMPROVEMENTS AND AT HIS COST TO THE CITY.
  - CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE CITY OF RIVERSIDE DEPARTMENT OF PUBLIC WORKS, STANDARD SPECIFICATIONS AND THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, 1976 EDITION.
  - TRIM EDGE OF EXISTING PAVEMENT WHERE NEW PAVEMENT JOINS TO A SMOOTH STRAIGHT LINE. CONSTRUCT PATCH-UP PAVING AS SHOWN ON PLAN AND OVERLAY PAVING AS DIRECTED IN THE FIELD TO PRODUCE A SMOOTH SECTION. ENGINEER ESTIMATES OVERLAY TO BE 1" THICK.
  - CURBS AND GUTTERS SHALL BE STAKED WITH 5' OFFSETS AT 25' INTERVALS.
  - ALL FINISHED ELEVATIONS SHALL BE STAKED IN THE FIELD BY THE PRIVATE ENGINEER.
  - INSTALL 6" HIGH CHAIN LINK FENCE AT REAR PROPERTY LINE ALONG AT S.S.F. R/W.
  - THE CONTRACTOR SHALL CONTACT THE PUBLIC SERVICES DEPARTMENT (787-7531) TO CHECK ON ANY EXISTING SIDE AND BACKLASHES THAT ARE BEING RETAINED. THE CITY'S INSPECTOR WILL MAKE THE FINAL DETERMINATION ON WHETHER A BACKLASH CAN BE RELOCATED.
  - LOCATION OF SEWER TAPERS TO BE DETERMINED IN THE FIELD AT THE DISCRETION OF THE ENGINEER. AVOID CONFLICT WITH ADJACENT AND/OR EXISTING FACILITIES.

