



NOTE:  
 Turn edge of existing paving to clean straight line 2' from top of gutter (2' from curb face) place match-up paving 5' shown and overlay existing paving as directed in this field to produce a smooth convex surface.

**GENERAL NOTES**

- All construction shall be in accordance with Standards and Specifications No. 46 of the City of Riverside Department of Public Works.
- It shall be the responsibility of the Contractor to clear the Right of Way in accordance with the provisions of law as it affects such utility, including irrigation lines and appurtenances, and at no extra cost to the City of Riverside.

BENCH MARK: E.L. spike in guy pole No. 20280-N on turn 600' S. of John Street on West side Victoria Ave. front of house numbered 1091 Victoria. ELEV. 853.57'

T.B.M. 19' spike in P.R. No. 2635-J. at angle point in pole line (J.R.D. R. 754-10) ELEV. 852.19'

TRAFFIC DIV. Approved 10/21/63 Date	PAVE DEPT. Approved Date	<b>J. F. DAVIDSON - CIVIL ENGINEER</b> R.E. NO. 852 RIVERSIDE, CALIFORNIA APPROVED BY: <i>[Signature]</i> DATE: 10-2-63
<b>REVISIONS</b> MARK DATE DESCRIPTION		
CITY OF RIVERSIDE, CALIFORNIA DEPARTMENT OF PUBLIC WORKS <b>STREET PLAN &amp; PROFILE</b> <b>VICTORIA AVENUE</b> STA 356+80.00 TO 358+13.00		HORIZ. SCALE 1" = 10' VERT. SCALE 1" = 4' DESIGNED BY: [Signature] DRAWN BY: [Signature] RECOMMENDED BY: [Signature] ASSISTANT CITY ENGINEER APPROVED BY: [Signature] Director of Public Works DATE: 10-2-63 NO. <b>R-516-A</b> SHEET 1 OF 1