



NOTE: Match up paving to be 5\"/>

- INDEXED 50
- GENERAL NOTES
- All construction shall be in accordance with Standards or Specifications No. 401 of the Riverside Department of Public Works.
 - The contractor shall be responsible for the location of all existing utilities and for the protection of same. The contractor shall be responsible for the location of all existing utilities and for the protection of same.
 - Trim edge of existing pavement, where new paving joins existing pavement, to a clean, straight line. Construct match-up paving as shown and overlay paving as directed in the field to produce a smooth crown section, prime coat, seal coat and paint binder are required.
 - Grading will require a permit under Ordinance 3093 for a cut or fill exceeding 100 cubic yards, or a fill over one foot in depth.

Howell K. O'Brien 6-4-64 IRRIGATION ENGINEER DATE
 B.M. Nail in B.C.R. N.Y. curb at N.E. Cor. Bonita & Riverside Avenues. - Elev. 540.40
 B.M. PK nail in N.W. C&G Ref. of Bryce Way & Riverside Avenue. - Elev. 547.82

J. F. DAVIDSON ASSOCIATES CIVIL ENGINEERS - SURVEYORS - PLANNERS RIVERSIDE, CALIFORNIA APPROVED BY <i>J. F. Davidson</i> DATE 4-22-64 R.E. No. 382 W.O. 12250 FOR Joseph Taravellano Sr. F.B. 548	Relocate Driveway Approach Riv. City Std. No. 302	CITY OF RIVERSIDE, CALIFORNIA DEPARTMENT OF PUBLIC WORKS		STREET PLAN AND PROFILE RIVERSIDE AVENUE RECORD OF SURVEY No. 810	PROJECT NO. R-858
	MARK REVISIONS APPR. DATE DESIGNED BY _____ DRAWN BY _____ CHECKED BY _____	APPROVED BY _____ DATE 6-11-64 OFFICE ENGINEER PARK DEPARTMENT TRAFFIC DIVISION ASSISTANT CITY ENG.	APPROVED BY _____ DATE 6-11-64 DIRECTOR OF PUBLIC WORKS	SHEET 1 OF 1 FILE NO. 2754	HORIZ. SCALE: 1" = 50' VERT. SCALE: 1" = 5'