



MAP SHOWING IMPROVEMENTS TO BE MADE ON TWELFTH STREET FROM MAIN ST. TO LEMON.
 A P CAMPBELL, CITY ENGINEER

EXPLANATORY NOTES OF WORK TO BE DONE

1. Catch basins to be constructed according to diagram No 2 and specifications No 23.

2. Curb and gutter to be constructed according to diagram No 1 and specifications No 22 for the curb portion and specifications No 23 for the gutter portion as shown.

3. Special curbs to be constructed according to specifications No 24 as shown.

4. Type E catch basins to be constructed according to diagram No 2 as shown.

5. 10" Vitrified Pipe Drains to be constructed connecting the Type E catch basins to the drainage ditch as shown.

6. Alley Drains to be constructed according to diagram No 3 and lettered as shown.

7. Special curb and gutter to be constructed at the intersection of Twelfth & Orange streets according to diagram No 4 and specifications No 22 and 23 as shown.

Approved by the Mayor and Common Council of the City of Pasadena this 25th day of May 1906.

Attest: *[Signature]* City Clerk

DIAGRAM NO 5
 CROSS SECTION OF A PORTION OF MACADAM ROADWAY showing thickness of macadam and order of applying screenings and oil. The surface of the macadam shall be level with the top of the gutter edge and the finished grade marked when compacted ready for the oil and screenings. Rock shall be 2 and 3 inch rock. One quarter (1/4) inch screenings shall be used.