



GENERAL NOTES

1. Construction shall be in accordance with the City of Riverside, Dept. of Public Works Standard Drawings and the Standard Specifications for public works construction 1973 edition.
2. The contractor is to verify Existing Sewer Elevations prior to construction.
3. The sewer contractor shall adjust manholes to final grade after paving is completed.
4. A plug shall be installed and will remain in place where the new sewer connects with the existing sewer until the new sewer is accepted by the City of Riverside, California.

B.M.

Rim of Capped Monument of intersection of Horace Street and Victoria Avenue per City of Riverside Drawing R-727.

T.B.M.

(This Project only)
 T.B.M.-A - Chiseled "a" Center of Curb outlet Box 20' S 1/4 of the E of Horace Street and 30' W 1/4 of Canal per J.F.D. F.B. 834/28
 ELEV. = 1011.16'

APPROVED BY: *[Signature]* 1-13-76
 Chief Public Utilities Engineer Date

J. F. DAVIDSON ASSOCIATES
 CIVIL ENGINEERS - SURVEYORS - PLANNERS
 RIVERSIDE, CALIFORNIA

APPROVED BY: *[Signature]* DATE 1-9-76
 R.E. No. 13697

W.O. 4430 FOR R.S. WHITE F.B./093/12

MARK	REVISIONS	APPR. DATE

DESIGNED BY R.L.S. DRAWN BY W.W. CHECKED BY

CITY OF RIVERSIDE, CALIFORNIA
 DEPARTMENT OF PUBLIC WORKS

APPROVED BY: *[Signature]* DATE 3-9-76
 PRINCIPAL ENGINEER
 PARK DEPARTMENT
 TRAFFIC DIVISION
 CHIEF P. W. ENGR.

SEWER PLAN & PROFILE

TRACT 6829
 APPIAN WAY
 AMY STREET

INDEXED R.B. PROJECT NO. S-1027
 SHEET 1 OF 1
 FILE NO. 4980

HORIZ. SCALE: 1" = 40' VERT. SCALE: 1" = 4'