



- NOTE:
1. DIMENSIONS, ELEVATIONS, AND STATIONS ARE OFF THE EXISTING SEWER LINE; THEY MAY NEED TO BE ADJUSTED IN THE FIELD.
 2. FOR VERTICAL AND HORIZONTAL ANGLES FOR LAYING PIPE SEE SPECIAL PROVISIONS.
 3. SEWAGE MUST BE CONTAINED IN CLOSED CONDUITS AT ALL TIMES.
 4. FOR LOCATION SEE VICINITY MAP IN SPECIAL PROVISIONS.
 5. REMOVE EXISTING SEWER AND MANHOLES WITHIN CONSTRUCTION LIMITS. CONCRETE BACKFILL IS TO BE IN FIRM MATERIAL; LIMITS DEPEND ON MATERIAL ENCOUNTERED.
 6. ENCASEMENT & WALLS ARE SHOWN IN PROFILE ONLY.
 7. 10" SEWER SHALL BE ABS "TRUSS PIPE".

CITY OF RIVERSIDE DOMESTIC SYSTEM
Wesley E. Hahn 3-20-78
 CHIEF UTILITIES ENGINEER, WATER

CURVE DATA				
INDEX	R	Δ	T	L
1	300'	21° 50' 00"	57.86'	114.32'
2	300'	32° 03' 25"	57.16'	111.90'

MARK	REVISIONS	APPR.	DATE

CITY OF RIVERSIDE
 PUBLIC WORKS DEPARTMENT
 APPROVED BY: *[Signature]*
 TRAFFIC DIVISION: *[Signature]*
 CHIEF P. W. ENGINEER: *[Signature]*
 SEWER DIVN. DATE: 5/13/78

BENEDICT CANYON SEWER REPLACEMENT
 (SOUTH OF CHICAGO AVE)
 ACCOUNT NO. 32-577-502
S-1160
 SHEET 1 OF 1
 FILE NO. _____
 HORIZ. SCALE: 1" = 40'
 VERT. SCALE: 1" = 4'

*AS BUILT 8/15/78 R.P.R.