



CONSTRUCTION NOTES

- CONSTRUCTION SHALL BE IN ACCORDANCE WITH STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, 1979 EDITION.
- THE FOLLOWING STD. DWGS APPLY:
 - 452 - PIPE BEDDING
 - 453 - TRENCH BACKFILL
 - 500 - MANHOLE
 - 502 - SEWER LATERAL

10+20 ± CONST. 4" H.C. DEPTH @ 12" TO BE 8"

10+25 CONST. M.H. AS PER STD. DWG. NO. 500.

CITRUS STREET

BENCH MARK CITY OF RIV. 601-G-68
 BRONZE DISK IN CONC. POST ABOUT 1.1 MILES SW ALONG AT & SP R.R. FROM THE CROSSING OF CENTER STREET AT HIGH GROVE, 0.2 MILES SW OF THE PALMYRITA AVE. CROSSING, 20' NW OF THE NW RAIL, 66.5' NE OF PP 25151J, 50' NE OF A CONC. CONTROL BOX. STD. DISK IN CONC. POST 4' LOWER THAN THE TRACK GUARD POST 2' SW OF MONUMENT. ELEV. 898.646

CITY OF RIVERSIDE, CALIFORNIA DEPARTMENT OF PUBLIC WORKS				SEWER PLAN & PROFILE		PROJECT NO. 32-575-547	
APPROVED BY _____ BY _____ DATE _____				APPROVED BY _____		CITRUS STREET	
PRINCIPAL ENGINEER				PARK DEPARTMENT		SEWER EXTENSION	
TRAFFIC DIVISION				DIRECTOR OF PUBLIC WORKS		475' TO 205' W'LY OF IOWA AVENUE	
DESIGNED BY _____ DRAWN BY _____ CHECKED BY _____				DATE _____		HORIZ. SCALE: 1" = 20' VERT. SCALE: 1" = 4'	
MARK REVISIONS APPR. DATE				FILE NO.		SHEET 1 OF 1	

ADAPTED FROM PLAN 5-1222