



- GENERAL NOTES**
1. Construction shall be in accordance with City of Riverside Dept. of Public Works Specifications No. 460 and Standard Drawings.
 2. Location of wyes and laterals to be determined in field.
 3. All stubs and laterals to be constructed in accordance with Standard Drawing No. 562. Stubs shall be plugged and capped.
 4. Pipe shall be bedded in accordance with Case II, Std. Dwg. No. 452.
 5. Boring under the canal shall be done in accordance with the specifications of the Riverside Water Company.

BENCH MARK
 N.P.F. in P.P. #707AJ - 1st Pole North of Canal on East side of Tyler St. Elev. 791.09. F.O. 1911A*3/2 #432/1A.

Approved *Tom Campbell* Date 8/30/61
 City Irrigation Division

ALBERT A. WEBB ASSOCIATES
 CIVIL ENGINEERS - RIVERSIDE, CALIFORNIA
 Approved *Albert A. Webb* DATE 8/9/61
 E.E. 2376

REVISION		DESCRIPTION
MARK	DATE	

DATE	Aug. 1961	SCALE	Horiz. 1"=50'
DRAWN	REC	W.D.	60-258
CHECKED	D.R.B. C.F.	F.B.	432

APPROVED BY	<i>Tom Campbell</i>	NO. S-296
DIRECTOR OF PUBLIC WORKS		SHEET 1 OF 1
DATE	Sept 8 1961	

QUANTITY ESTIMATE

8" Vitriified Clay Pipe	796 lin. ft.
4" Vitriified Clay Pipe	435 lin. ft.
16"x16" Waled Steel Pipe	30 lin. ft.
8"x8"x4" Wyes	7
Std. No. 500 Manholes	3
Std. No. 502 Drop Manhole	1

* = As Built 6/4/62 RK

PROFILE
 SURVEYED
 PLOTTED
 ALIGNED CHECKED
 R. M. WOOD
 STRUCTURE NOTATION: CH. 10

PLAN
 SURVEYED
 PLOTTED
 ALIGNED CHECKED
 R. M. WOOD
 STRUCTURE NOTATION: CH. 10