



- GENERAL NOTES**
1. No wyes or laterals to be const on this project. All manholes to be Riverside City Standard No. 302, unless otherwise noted on plan. Maximum vertical spacing of steps in all manholes shall be 12".
 2. All construction shall be in accordance with Standards and Specifications No. 61 of the City of Riverside Department of Public Works. Pipe shall be bedded per Case II, Standard Drawing No. 432.
 3. It shall be the responsibility of the contractor to clear the Right of Way in accordance with the provisions of law as it affects each utility, including irrigation lines and appurtenances, and at no extra cost to the City of Riverside.
 4. Joints in vitrified clay pipe sewers shall conform to ASTM standard C-425-60 T, or the latest revision thereto.
 5. One lane in each direction shall be kept open at all times on Victoria Ave.
 6. J.F. Davidson, C.E. (Tele. 0V6-0844) shall be notified 48 hours prior to any construction staking for this sewer.

INDEXED PER **F.B. 787-47**
F.B. 780

City & M. - Lead & back in center of curb return at S.W. cor. of Laramie Road & Victoria Avenue. Elev. = 938.569

J. F. DAVIDSON - CIVIL ENGINEER
R.E. NO. 862
RIVERSIDE, CALIFORNIA

APPROVED BY *J.F. Davidson* DATE 10/1/63

CITY OF RIVERSIDE, CALIFORNIA
DEPARTMENT OF PUBLIC WORKS

SEWER PLAN & PROFILE
VICTORIA AVENUE
LARAMIE RD. TO 235 FT. NORTH
RIVERSIDE HIGH SCHOOL DIST.
HORIZ. SCALE 1" = 40' VERT. SCALE 1" = 4'

MARK	DATE	DESCRIPTION
①	4/30/64	M.H. # 2 Sta. 2+06.00 REVI. JFM by wds Approved

DESIGNED BY
DRAWN BY
CHECKED BY *wds*
DATE 3/3/64

APPROVED BY *J.F. Davidson*
DATE 3/3/64

NO. **5-417**
SHEET 1