



- GENERAL NOTES**
1. All Construction shall be in accordance with Standards and Specifications No. 461 of the Riverside Department of Public Works. Pipe shall be bedded per Case II, Standard Drawing No. 452.
 2. It shall be the responsibility of the Contractor to clear the provisions of law as it affects each utility including and at no extra cost to the City of Riverside.
 3. ALL laterals to be 4" and extend to property line. Laterals to be located in field.
 4. BENCH MARK: Square bolt at intersection of HOLE & TYLER. Elev 738.62.
 5. Joints in vitrified clay pipe sewers shall conform to A.S.T.M. Standard C-425-60T or the latest revision thereto.

J. F. DAVIDSON - CIVIL ENGINEER
 R.E. NO. 862
 RIVERSIDE, CALIFORNIA
 APPROVED BY *J. J. Sanders* DATE 2-5-1964

REVISIONS	
E	DESCRIPTION

CITY OF RIVERSIDE, CALIFORNIA
DEPARTMENT OF PUBLIC WORKS

SEWER PLAN & PROFILE
HOLE AVENUE
 FROM 90' TO 380' WLY OF TYLER ST.
 1" = 40' 1" = 4'
 HORIZ. SCALE VERT. SCALE

CHECKED BY *Ed. W. ...*
 APPROVED BY *J. J. Sanders*
 Director of Public Works
 DATE 3-24-64

NO. **S-462**
 SHEET 1 1

As Built 5-1-64 BE