



- GENERAL NOTES**
- All wires and laterals to be located in the field. All manholes to be Riverside City Standard No. 502, unless otherwise noted on plan. Maximum vertical spacing of steps in all manholes shall be 12".
 - All Construction shall be in accordance with Standards and Specifications No. 161 of the City of Riverside Department of Public Works. Pipe shall be bedded per Case II, Standards Drawing No. 362.
 - It shall be the responsibility of the Contractor to clear the Right of Way in accordance with the provisions of law as it affects each utility including their respective easements and appurtenances, and at no extra cost to the City of Riverside.

B.M.: Pk. nail in Nly. curb of Magnolia Avenue, approx 70' Wly. of E. of Jefferson Street Elev. = 793.135

J. F. DAVIDSON - CIVIL ENGINEER
R.E. NO. 862
RIVERSIDE, CALIFORNIA

APPROVED BY *J. F. Davidson* DATE 7-26-64

REVISIONS		
MARK	DATE	DESCRIPTION

CITY OF RIVERSIDE, CALIFORNIA
DEPARTMENT OF PUBLIC WORKS

SEWER PLAN & PROFILE
VIA SAN JOSE - COLEMAN ST.

RECORD OF SURVEY N° 779
HORIZ. SCALE 1" = 40' VERT. SCALE 1" = 4'

DESIGNED BY
DRAWN BY
RECOMMENDED BY *A. A. Chual* ASSISTANT CITY ENGINEER

CHECKED BY *W. J. B.*

APPROVED BY *J. F. Davidson* Director of Public Works

DATE 7-23-64

NO. 5-531 SHEET 1 1