



GENERAL NOTES

- CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, 1973 EDITION AND CITY OF RIVERSIDE STANDARD DRAWINGS.
- IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO CLEAR THE RIGHT OF WAY IN ACCORDANCE WITH THE PROVISIONS OF THE LAW AS IT AFFECTS EACH UTILITY INCLUDING IRRIGATION LINES AND APPURTENANCES.
- PIPE SHALL BE BEDDED PER STANDARD DRAWING NO. 452, CASE 2, UNLESS OTHERWISE SPECIFIED ON THE PLAN.
- INSTALL WYES WHERE SHOWN ON THE PLANS.
- PRIOR TO CONSTRUCTION OF SEWER, CONTRACTOR IS TO EXPOSE EXISTING SEWER AND CONTACT THE ENGINEER FOR VERIFICATION OF STUB ELEVATION.
- AT ALL HOUSE LATERAL OR SEWER MAIN CROSSINGS OF WATER MAINS, SHOWN THE SEWER SHALL BE ENCASEMENT PER STD. DWG. CWD-023 FOR 4.50' EACH SIDE OF WATER MAIN.
- A PLUG SHALL BE INSTALLED AND WILL REMAIN IN PLACE WHERE THE NEW SEWER CONNECTS WITH THE EXISTING SEWER UNTIL SUCH A TIME THAT THE NEW SEWER IS ACCEPTED BY THE CITY.
- THE CONTRACTOR SHALL EXPOSE THE STORM DRAIN LATERAL WHERE THE SEWER CROSSES IT & HAVE THE ENGINEER VERIFY THE LOCATION OF THE STORM DRAIN LATERAL PRIOR TO THE START OF CONSTRUCTION.
- IF SEWER IS CONSTRUCTED FROM 6+50.30 NLY MEET EXIST. 8" VCP IF NOT PLUG PROP SEWER WITH A REMOVABLE PLUG.

NOTICE TO CONTRACTOR

THE EXISTENCE AND LOCATION OF ANY UNDERGROUND UTILITY PIPES OR STRUCTURES SHOWN ON THIS PLAN WERE OBTAINED BY A SEARCH OF THE AVAILABLE RECORDS. TO THE BEST OF OUR KNOWLEDGE, THERE ARE NO EXISTING UTILITIES EXCEPT AS SHOWN ON THESE PLANS.

THE CONTRACTOR IS REQUIRED TO TAKE DUE PRECAUTIONARY MEASURES TO PROTECT THE UTILITY LINES SHOWN AND ANY OTHER LINES NOT OF RECORD OR NOT SHOWN ON THIS PLAN.

CURVE DATA			
NO.	R	Δ	T
1	280'	14°24'10"	35.38'
2	304'	21°48'10"	58.55'
3	300'	21°48'10"	57.78'

- A PLUG SHALL BE INSTALLED AND WILL REMAIN IN PLACE WHERE THE NEW SEWER CONNECTS WITH THE EXISTING SEWER UNTIL SUCH A TIME THAT THE NEW SEWER IS ACCEPTED BY THE CITY.
- THE CONTRACTOR SHALL EXPOSE THE STORM DRAIN LATERAL WHERE THE SEWER CROSSES IT & HAVE THE ENGINEER VERIFY THE LOCATION OF THE STORM DRAIN LATERAL PRIOR TO THE START OF CONSTRUCTION.
- IF SEWER IS CONSTRUCTED FROM 6+50.30 NLY MEET EXIST. 8" VCP IF NOT PLUG PROP SEWER WITH A REMOVABLE PLUG.

ALBERT A. WEBB ASSOCIATES
CIVIL ENGINEERS
RIVERSIDE, CALIFORNIA

APPROVED BY: *[Signature]* DATE: 2/26/74
R.E. No. 21884

DESIGNED BY: *[Signature]* DRAWN BY: *[Signature]* CHECKED BY: *[Signature]*

APPROVED BY: *[Signature]* DATE: 12-13-74
CHIEF WATER UTILITY ENGINEER

CITY OF RIVERSIDE, CALIFORNIA
PUBLIC WORKS DEPARTMENT

APPROVED BY: *[Signature]* DATE: 1-20-75
CHIEF PUB. WKS. ENGR.

SEWER PLAN AND PROFILE
SANDY LANE
SEWER EXTENSION
BETWEEN ARLINGTON AVE. AND VALLEY DR.
PARCEL MAP 202

ACCOUNT No. 32-517-55A
DRAWING NUMBER
S-992
SHEET 1 OF 1
74-223-B

SCALE: Horiz. 1" = 40', Vert. 1" = 4'