



(7) The finished sub grade shall have a connection of not less than 100% for a depth of 60 feet as determined by test method No. 2025 immediately prior to placement of the cover.  
 (8) Approx. 7.5 tons of A.C. overlay are required for P.C. 25.000.

**QUANTITY ESTIMATE**  
 FOR R.S. 893  
 Curb & Gutter Standard No. 200 (6" C.C.)

196 L.F.
5553 S.F.
62 L.F.
1234 S.F.
18 L.F.
2 S.F.
30 L.F.

**ALBERT A. WEBB ASSOCIATES**  
 CIVIL ENGINEERS  
 RIVERSIDE, CALIFORNIA  
 APPROVED BY: *[Signature]* DATE: 3/1/65  
 R.E. No. 2876  
 W.G. 65-14 FOR LONNIE L. LAMBETH P.B. 364

NO.	REVISIONS	DATE
1	ADDED A.C. OVER CURB	7/21/67
2	ADDED A.C. OVER CURB	7/21/67
3	ADDED A.C. OVER CURB	7/21/67

**CITY OF RIVERSIDE, CALIFORNIA**  
 DEPARTMENT OF PUBLIC WORKS  
 APPROVED BY: *[Signature]* DATE: 4-30-65  
 ASSISTANT CITY ENGINEER

**STREET PLAN AND PROFILE**  
**GRATTON STREET**  
 WESTERLY SIDE, 1150.50'  
 SOUTHERLY OF DUFFERIN  
 R.S. No. 893 & 980  
 HORIZ. SCALE: 1" = 50' VERT. SCALE: 1" = 5'

**PROJECT NO.**  
**R-1033**  
**SHEET 1 OF 1**  
**FILE NO. 65-14-A**