



- CONSTRUCT CURB & GUTTER PER C/R STD. DRW. NO. 200, 6" CF
- CONSTRUCT CURB, GUTTER, & SIDEWALK PER C/R STD., 6" CF DRW. NO. 325
- LIMITS OF AC REMOVAL
- CONSTRUCT AC OVERLAY
- CONSTRUCT 4 1/2" AC OVER 11 1/2" DG
- USE 3" AC OVER 8" BASE ON SHEPPARD ST.
- 2" AC ON COMPACTED STERILIZED SOIL
- PLACE AC FULL DEPTH TO TOP OF BALLAST
- REMOVAL OR RELOCATION AND CONSTRUCTION BY R.R.

Curve Data				
No.	A	R	T	L
①	137°05'39"	15'	38.17	35.89
②	40°54'05"	35'	13.05	24.97
③	29°22'49"	33'	6.64	16.32

Typical Cross Section

FOR STORM DRAIN SEE DWG. D-165

CITY OF RIVERSIDE, CALIFORNIA
DEPARTMENT OF PUBLIC WORKS

JURUPA AVE. AT
UPRR. (GATES)

PROJECT NO. 3141
R-1274

APPROVED BY: [Signature]
DATE: 5-16-69

DESIGNED BY: [Signature] DRAWN BY: [Signature] CHECKED BY: [Signature]

HORIZ. SCALE: 1" = 20' VERT. SCALE: 1" = 2'