



- CONSTRUCTION NOTES**
1. CONST. 2 1/2" AC OVER 4" CLASS 3 A 3 (SEE GEN. NOTE #2)
 2. CONST. CURB & GUTTER STD. 20" (6" G)
 3. CONST. DRAINAGE LINE SIDEWALK PER STD. 350
 4. 12" 5" 0" 0" 11" 1/2" APPROACH PER STD. 308 (1" 22", 8" 36")
 5. CONST. GROSS GUTTER PER STD. 450
 6. PLACE 2" X 4" REDWOOD HEADER TO REMAIN
 7. INSTALL 4" BOR LIGHT REFLECTOR 3 EA @ 10' OC.

- GENERAL NOTES**
1. CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE CITY OF RIVERSIDE, DEPARTMENT OF PUBLIC WORKS SPECIFICATIONS AND STANDARD DRAWINGS
 2. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO CLEAR THE RIGHT OF WAY IN ACCORDANCE WITH THE PROVISIONS OF THE PLAN AS IT AFFECTS EACH UTILITY INCLUDING IRRIGATION LINES AND APPURTENANCES AND AT NO COST TO THE CITY
 3. PRIME COAT, SEAL COAT AND PAINT BINDER ARE REQUIRED.
 4. TRIM EDGE OF EXISTING PAVEMENT WHERE NEW PAVEMENT JOINS EXISTING PAVEMENT TO A CLEAN STRAIGHT EDGE. CONSTRUCT MATCH-UP PAVING AS SHOWN AND DISPLAY AS DIRECTED IN THE FIELD TO PRODUCE A SMOOTH CROWN SECTION. ENGINEER ESTIMATES THE OVERLAY PAVEMENT TO BE (UNDES 1.75M).
 5. THE DEVELOPER SHALL ARRANGE FOR A SOIL TEST AT SUB GRADE LEVEL BY A SOILS ENGINEER. THICKNESS OF PAVEMENT & TYPE OF AGGREGATE BASE SHALL BE DETERMINED BY THE SOILS ENGINEER AND SUBMITTED TO THE CITY OF RIVERSIDE FOR APPROVAL PRIOR TO CONSTRUCTION.

BENCH MARK C/R H.B. 5607
 5" LL IN 5" CURB/HOFFMAN AVE. APPROX. 1/4" (S&W) OF BERNARD ST.
 ELEV. 820.30

TYPICAL SECTION - BERNARD STREET
 STA. 2150 TO STA. 2155
 SCALE: 1" = 5'

CRAWLEY HAWKINS & ASSOC.
 ENGINEERS & SURVEYORS
 RIVERSIDE, CALIFORNIA

APPROVED: *[Signature]*
 DATE: 10-15-88
 FOR DANA HORN

CITY OF RIVERSIDE, CALIFORNIA
 DEPARTMENT OF PUBLIC WORKS

APPROVED BY: *[Signature]*
 DATE: 10-15-88

DESIGNED BY: G.H. DRAWN BY: G.H. CHECKED BY: G.H.

STREET PLAN & PROFILE
BERNARD STREET
 NORTHEASTERLY SIDE
 FROM 259' TO 608' S&W OF INDIANA AVE.
 ZONING CASE R-21-690

HORIZ. SCALE: 1" = 40' VERT. SCALE: 1" = 4'

PROJECT NO. **R-1409**
 SHEET. 1 OF 1
 FILE NO. 4171