



CURVE DATA
 @ R. 25.00
 Δ = 27°05'
 T = 6.25'
 L = 11.82'

@ R. 22.00
 Δ = 17°25'11"
 L = 10.87'

- GENERAL NOTES**
1. All construction shall be in accordance with Standards and Specifications No. 460 of the City of Riverside Department of Public Works.
 2. It shall be the responsibility of the Contractor to clear the Right of Way in accordance with the provisions of law as it affects each utility, including irrigation lines and appurtenances, and at no extra cost to the City of Riverside.
 3. If the Subdivider desires to reduce requirement on import base material, additional soil tests may be taken at the Subdivider's expense after streets are prepared to rough grade. Subdivider will contact Inspection Division, City of Riverside, before making test. The City of Riverside will make a test of base material in place. Before paving can be installed, results of this test must indicate that the base material is satisfactory to the Inspection Division.
 4. BENCH MARK - U.S.C. & G. brass cap in well at N.W. corner of Brockton and Arlington Ave. Elevation 843.245.
 - 5.

J. F. DAVIDSON - CIVIL ENGINEER
 R.E. NO. 862
 RIVERSIDE, CALIFORNIA
 APPROVED BY *George E. M. Cook* DATE 7/1/61
 22. 1960

REVISIONS		
MARK	DATE	DESCRIPTION

CITY OF RIVERSIDE, CALIFORNIA
DEPARTMENT OF PUBLIC WORKS

STREET PLAN & PROFILE
ALLEY - 222.53' N.W. of Arlington Ave & From Brockton Ave. to 357' ELY.

REZONING CASE R-68-589
 HORIZ. SCALE 1"=40' VERT. SCALE 1"=4'

DESIGNED BY
 DRAWN BY
 RECOMMENDED BY *A. S. Johnson*
 ASSISTANT CITY ENGINEER

CHECKED BY *W. J. ...*
 DIRECTOR OF PUBLIC WORKS

APPROVED BY *J. F. Davidson*
 CIVIL ENGINEER

DATE 7-1-61 SHEET 1 OF 1

NO. R-475

