



GENERAL NOTES

- All Construction shall be in accordance with Standards and Specifications No. 461 of the City of Riverside Department of Public Works.
- It shall be the responsibility of the Contractor to clear the Right of Way in accordance with the provisions of law as it affects each utility including irrigation lines and appurtenances, and set no extra work to the City of Riverside.
- Grading will require a permit under Ordinance 3073 for a cut or fill exceeding 100 cubic yards, or a fill over one foot in depth.
- The City of Riverside will take a soil test to determine the requirement on imported base material after the street has been prepared to rough grade.
- Prims coat, seal coat, and paint binder are required.
- Trim edge of existing pavement where new paving joins existing pavement to a clean straight line. Construct match-up paving as shown and overlay paving as directed in the field to produce a smooth crown section.

B.M. Top of W.C. Bolt in Flange of Fire Hydrant at SW Cor. Brockton and Rubidoux Avenues. Elev. = 825.68

REVISIONS	
MARK	DESCRIPTION

J. F. DAVIDSON - CIVIL ENGINEER
 R.E. NO. 862
 RIVERSIDE, CALIFORNIA
 APPROVED BY *[Signature]* DATE 12-3-63
CITY OF RIVERSIDE, CALIFORNIA
DEPARTMENT OF PUBLIC WORKS
 STREET PLAN & PROFILE
RUBIDOUX AVENUE
ZONING CASE R-50-623
 HORIZ. SCALE 1" = 20' VERT. SCALE 1" = 4'

DESIGNED BY: *[Signature]*
 DRAWN BY: *[Signature]*
 CHECKED BY: *[Signature]*
 RECOMMENDED BY: *[Signature]*
 ASSISTANT CITY ENGINEER

APPROVED BY: *[Signature]*
 DIRECTOR OF PUBLIC WORKS
 DATE: 5-24-64
 SHEET 1 OF 1

