



2. Prime coat, seal coat, and paint binder are required.
3. bility
4. Grading will require a permit under Ordinance 3093 for a cut or fill exceeding 100 cubic yards, or a fill over one foot in depth.
5. Imported Base Material requirement to be determined by Subdivider's Soil Engineer. Recommendations for I.B.M. to be approved by City of Riverside prior to paving.
6. Trim edge of existing pavement, where new paving joins existing pavement, to a clean, straight line. Construct match-up paving as shown and overlay paving as directed in the field to produce a smooth crown section.
7. Manholes to be adjusted to grade after streets are paved.
8. Furnish and install street name signs and posts as per Riverside City Std. Dwg. No. 662. See sign schedule on sheet 2.

J. F. DAVIDSON ASSOCIATES CIVIL ENGINEERS - SURVEYORS - PLANNERS RIVERSIDE, CALIFORNIA		CITY OF RIVERSIDE, CALIFORNIA DEPARTMENT OF PUBLIC WORKS		PROJECT NO. R-865
APPROVED BY: <i>George M. [Signature]</i> R.E. No. 10688	DATE: 3/1/64	APPROVED BY: <i>[Signature]</i> OFFICE ENGINEER: 5-306 PARK DEPARTMENT: 5-215/184 TRAFFIC DIVISION: 5-215/184 ASSISTANT CITY ENG.	DIRECTOR OF PUBLIC WORKS	SHEET 1 OF 2
W.O. 12244 FOR: M & G, Inc.	F.B. 794-70	DESIGNED BY: EJM DRAWN BY: EJM CHECKED BY:	DATE: 5-21-64	FILE NO. 2749

